



BWAY Cable & Wire Ltd

Unit D, 22/F, Kin Ga Industrial Building,
No.9 San On Street, Tuen Mun, NT, Hong Kong

Web: www.bma-tech.com

Tel: (852) 2488 5200 Fax: (852) 2488 5882

E-Mail: sales@bma-tech.com

salesdg@bma-tech.com

Specification

Style Number: UL1061

Conductor			Insulation		Conductor Resistance 20°C(Ω/KM)
AWG-No.	Construction	CON.DIA	Diameter	Tolerance	
30	7/0.10	0.31	0.80	±0.1	381.00
28	7/0.127	0.39	0.90	±0.1	237.25
26	7/0.16	0.49	1.00	±0.1	150.00
24	11/0.16	0.61	1.15	±0.1	94.20
22	17/0.16	0.76	1.25	±0.1	59.40
20	21/0.18	0.95	1.50	±0.1	36.70
18	34/0.18	1.21	1.80	±0.1	23.20
16	65/0.16	1.49	2.10	±0.15	14.60
Material of conductor: Stranded Tinned Copper					
Rated Temperature: 80°C					
Rated Voltage: 300V					
Material of insulator: SR PVC					
Color(s): BLACK, BROWN, RED, ORANGE, YELLOW, GREEN, BLUE, PURPLE, GRAY, WHITE, PINK					
Marking: E464676 AWM 1061 ()AWG 80°C 300V VW-1 --BWAY-- C AWM ()AWG I A 80°C 300V FT-1					
Construct map:					