



BWAY Cable & Wire Ltd

Unit D, 22/F, Kin Ga Industrial Building,
No.9 San On Street, Tuen Mun, NT, Hong Kong

Web: www.bma-tech.com



Tel: (852) 2488 5200 Fax: (852) 2488 5882

E-Mail: sales@bma-tech.com

salesdg@bma-tech.com

Specification

Style Number: UL1571

Conductor			Insulation		Conductor Resistance 20°C(Ω/KM)
AWG-No.	Construction	CON.DIA	Diameter	Tolerance	
30	7/0.10	0.31	0.80	±0.1	319.26
28	7/0.127	0.39	0.90	±0.1	197.94
26	7/0.16	0.49	1.00	±0.1	124.71
24	11/0.16	0.61	1.05	±0.1	79.36
Material of conductor:		Stranded Tinned Copper			
Rated Temperature:		80°C			
Rated Voltage:		30V			
Material of insulator:		PVC			
Color(s):		BLACK, GREEN, PINK	BROWN, BLUE,	RED, PURPLE,	ORANGE, GRAY, YELLOW, WHITE,
Marking:					
E464676  AWM 1571 ()AWG 80°C 30V VW-1 --BWAY-- C  AWM ()AWG I A 80°C 30V FT-1					
Construct map:					
