



**BWAY Cable & Wire Ltd**

Unit D, 22/F, Kin Ga Industrial Building,  
No.9 San On Street, Tuen Mun, NT, Hong Kong

Web: [www.bma-tech.com](http://www.bma-tech.com)

Tel: (852) 2488 5200 Fax: (852) 2488 5882

E-Mail: [sales@bma-tech.com](mailto:sales@bma-tech.com)

[salesdg@bma-tech.com](mailto:salesdg@bma-tech.com)

# Specification

Style Number: UL10720

Conductor			Insulation		Maximum Conductor Resistance 20°C(Ω/KM)
AWG-No.	Construction	CON.DIA	Diameter	Tolerance	
30	7/0.10	0.31	1.00	±0.10	397.00
28	7/0.127	0.39	1.10	±0.10	248.00
26	7/0.16	0.49	1.20	±0.10	152.00
24	11/0.16	0.61	1.30	±0.10	88.60
22	17/0.16	0.76	1.50	±0.10	62.50
20	21/0.18	0.95	1.70	±0.10	39.50
18	34/0.18	1.21	2.00	±0.15	24.40

<b>Material of conductor:</b>	Stranded Tinned Copper
<b>Rated Temperature:</b>	105°C
<b>Rated Voltage:</b>	300V

<b>Material of insulator:</b>	TPE
<b>Color(s):</b>	BLACK, BROWN, RED, ORANGE, YELLOW, GREEN, BLUE, PURPLE, GRAY, WHITE, PINK

**Marking:**  
E464676 AWM 10720 \*\* AWG 105°C 300V VW-1 --BWAY-- C AWM \*\* AWG I A 105°C 300V FT-1

**Remark** "" for 18~30

